





STAND ALONE ACCESS CONTROL & PANIC DEVICE

- **M9900LITE**
- **M9900DATA**
- **M9900PROX**

Lifetime Mechanical Warranty



M9900F		Specifications	
	<ul style="list-style-type: none">• Doors: 1-3/4" thick standard.• End cover: Flush mounted beveled "Panic Protector" design.• Strike: Roller strike.• Rail Assembly: Extruded Aluminum, 32D finish.• Dead latch Bolt: Stainless Steel 3/4" throw.• Dead latch Bolt: Stainless Steel 5/8".• Dogging feature: Allen Key (M9900)• UL listed: For "Panic Hardware" and Fire Rated Model 3 hour fire doors up to 38" x 86".• ANSI: ANSI 156.3 (2001), requirements for Grade 1.• 3 Hour Fire Rating• Finish: 32D		
IQ7LITE	Standard Features		
	<ul style="list-style-type: none">• CableGuard™ protects wires for easy installation• Standard ANSI door prep with one additional hole• Pre-programmed code• Keypad programmable• 160 User codes• Temporary user codes• Passage mode• Pin only mode• Double code entry for maximum security• Two wire remote release• 16 Digit tactile metal keypad• Weatherproof standard• Audible & visible entry indicator• Audible low battery alert• 4 "AA" batteries, 95,000 operations• Easy installation• Lifetime Mechanical Warranty• 2 Year Electronic Warranty		
IQ7DATA	<ul style="list-style-type: none">• CableGuard™ protects wires for easy installation• Weatherproof standard• Shielded electronics• 16 Digit tactile metal keypad• 320 User capability• 1600 Event audit trail• 160 Scheduled events• 32 Programmable holidays• Real time clock• Multiple entry codes for max security• Full scheduling features• Pin only• Terminator on/off• Built in relay• 3-10 Digit user code• Temporary user codes• First manager to arrive• Panic alarm interface• Two wire remote release• Fire tower lock function• Programmable by keypad or by use of the i-Dat software package• On-the-door upgradable memory• Privacy mode (<i>input to lockout keypad entry optional, consult factory</i>)• Scheduled/Manual passage mode• Audible & visible entry indicator• Audible low battery alert• 4 "AA" batteries included• Lifetime Mechanical Warranty; 2 Year Electronic Warranty• Additional Finishes, Consult Factory		
			
IQ7PROX	<ul style="list-style-type: none">• CableGuard™ protects wires for easy installation• Weatherproof standard• Shielded electronics• 16 Digit tactile metal keypad• 3008 User capability• 1180 Event audit trail• 1600 Scheduled events• 56 Programmable holidays• Real time clock• Multiple entry codes for max security• Full scheduling features• Pin only• Terminator on/off• Built in relay• 3-10 Digit user code• Temporary user codes• First manager to arrive• Panic alarm interface• Two wire remote release• Fire tower lock function• Accepts HID cards and fobs in 26, 33 and 37 format• Programmable by keypad or by use of the i-Dat software package• Privacy mode (<i>input to lockout keypad entry</i>)• Scheduled/Manual passage mode• Audible & visible entry indicator• Audible low battery alert• 4 "AA" batteries included• HI-SECURITY™ Cylinder Standard (Cylindrical Model Only)• Lifetime Mechanical Warranty; 2 Year Electronic Warranty• Additional Finishes, Consult Factory		
			
<u>IQ7 LITE Rim Exit Device Interface Specifications</u>		<u>IQ7 DATA Rim Exit Device Interface Specifications</u>	
Door Thickness: 1-3/4" standard; For thicker doors, Consult factory Handing: Non-handed Key Override: 1-1/8" Mortise cylinder, 6 pin w/2 keys Clutch: The "Clutch" for trouble free service		Door Thickness: 1-3/4" - 2-1/4" standard <i>Spacer kit available for thinner doors; For thicker doors consult factory.</i> Handing: Non-handed Key Override: 1-1/8" Mortise cylinder, Marks "C" Keyway, 6 pin w/2 keys, or 1-3/8", IC Core housing optional Clutch: The "Clutch" for trouble free service	
<u>IQ7 PROX Rim Exit Device Interface Specifications</u>			
Door Thickness: 1-3/4" - 2-1/4" standard <i>Spacer kit available for thinner doors; For thicker doors consult factory.</i> Handing: Non-handed Key Override: 1-1/8" Mortise cylinder, Marks "C" Keyway, 6 pin w/2 keys, or 1-3/8", IC Core housing optional Clutch: The "Clutch" for trouble free service			