



333 Bayview Avenue  
Amityville, New York 11701  
For Sales and Repairs, (800) 645-9445  
For Technical Service, (800) 645-9440  
Publicly traded on NASDAQ Symbol: NSSC  
© NAPCO 2010

# FWC-FSLC-RM2 Dual Relay Module DATA SHEET

WI1927 09/10

## ORDERING INFORMATION

**FWC-FSLC-RM2** - (Output device) Dual Relay Module provides two independently configurable Form C contacts per address, Contacts rated 1.0A @ 30VDC or 0.5A @ 125VAC.

For installation and wiring instructions, see WI1715.

## AGENCY LISTINGS

UL864 9th Edition: Commercial Fire

NFPA 72 National Fire Alarm Code

CSFM: California State Fire Marshall  
(Pending)

FM Approval: (Pending)

NYCFD: NYC Fire Department (Pending)

## SPECIFICATIONS

SLC Applied Voltage	Rated Range 25.3 – 39 VDC
SLC Current Consumption	Maximum 400µA Nominal 390µA
Relay Contact Ratings	1A @ 30VDC Power Factor 0.35 or 0.5A @ 120VAC Power Factor 0.35
Visual Indicator (Status LED)	bi-color LED – Green & Red Color & Mode – Selected and Programmed by Control Panel's software
Operating Temperature Range	0°C (32°F) ~ 49°C (120°F)
Storage Temperature Range	–30°C (–22°F) ~ 70°C (158°F)
Maximum Relative Humidity	Up to 90% RH non-condensing
Environment	Indoor dry use only
Dimensions	4.2"W X 4.7"H X .85"D
Weight	Approximately 3.0 ounces