



NAPCO®

333 Bayview Avenue
Amityville, New York 11701
For Sales and Repairs, (800) 645-9445
For Technical Service, (800) 645-9440
Publicly traded on NASDAQ Symbol: NSSC

© NAPCO 2010

FWC-FSLC-SOM1

Supervised Output Module

DATA SHEET

WI1929 09/10

ORDERING INFORMATION

FWC-FSLC-SOM1 - Supervised Output Module, provides a Class B Individual Circuit rated for 2A/30VDC.

For installation and wiring instructions, see WI1717.

AGENCY LISTINGS

UL864 9th Edition: Commercial Fire

NFPA 72 National Fire Alarm Code

CSFM: California State Fire Marshall (Pending)

FM Approval: (Pending)

NYCFD: NYC Fire Department (Pending)

SPECIFICATIONS

SLC Applied Voltage	Rated Range 25.3 – 39 VDC
SLC Current Consumption	Maximum 161µA Nominal 154µA
Auxiliary Applied Voltage	Nominal 24VDC
24VDC Auxiliary Current Consumption	1.15mA
Maximum Output Current (OUT+/OUT-, IN+/IN-)	2A @ 24VDC Power Factor 0.6
EOL Device for OUT+ & OUT-	NAPCO EOL Part No. 0400-02350 10KΩ
Visual Indicator (Status LED)	bi-color LED – Green & Red Color & Mode – Selected and Programmed by Control Panel's software
Operating Temperature Range	0°C (32°F) ~ 49°C (120°F)
Storage Temperature Range	-30°C (-22°F) ~ 70°C (158°F)
Maximum Relative Humidity	Up to 90% RH non-condensing
Environment	Indoor dry use only
Dimensions	4.2"W X 4.7"H X .85"D
Weight	Approximately 3.0 ounces